

### Product feature



1. Plastic polyurethane material conforms to the ROHS environment protection requirement.
2. High elasticity: small bend radius enables PU tubing to pass through the tight space.
3. Anti-knot: better anti-knot effect than other plastic tubing.
4. Excellent flexibility: it can bear repeated expansion.
5. Anti-abrasion: long working life and suitable for the environment in which it is easy to be worn.
6. Low permeability of gas: relieve the problems of leakage and pollution.
7. Good anti-solubility: no solvent leaks, therefore it will not pollute the environment.
8. Low compression: maintain excellent physical character.
9. Wide resistance: it has certain resistance to chemicals, water, fuel, oil and bacterium.

### Specification(Standard pressure type)

Type [Note1]	Tubing OD (mm)	Tubing ID (mm)	Wall Thickness (mm)	Package Length(m)	Working Pressure at 23°C(MPa)[Note2]	Burst pressure at 23°C(MPa)	Bend radius (mm)	Weight per 100M(kg)	Temperature (°C)
US98A032020□□	3.2	2.0	0.60	100/200	1.0	3.0	8	0.60	-20~70
US98A040025□□	4.0	2.5	0.75	100/200	1.0	3.0	10	0.94	
US98A060040□□	6.0	4.0	1.00	100/200	1.0	3.0	15	1.93	
US98A080050□□	8.0	5.0	1.50	100	1.0	3.0	20	3.66	
US98A100065□□	10.0	6.5	1.75	100	1.0	3.0	25	5.44	
US98A120080□□	12.0	8.0	2.00	100	1.0	3.0	35	7.56	
US98A160110□□	16.0	11.0	2.50	100	1.0	3.0	80	10.03	
UE95A032020□□	3.2	2.0	0.60	20/100/200	1.0	2.5	8	0.60	-40~70
UE95A040025□□	4.0	2.5	0.75	20/100/200	1.0	2.5	8	0.94	
UE95A060040□□	6.0	4.0	1.00	20/100/200	1.0	2.5	12	1.91	
UE95A080050□□	8.0	5.0	1.50	20/100	1.0	2.5	17	3.58	
UE95A100065□□	10.0	6.5	1.75	20/100	1.0	2.5	20	5.32	
UE95A120080□□	12.0	8.0	2.00	20/100	1.0	2.5	30	7.27	

[Note1] The first square of "□□" in the type column is for ordering code "unit" and the second is for "color".

[Note2] Working pressure:3 to 1 safety factor.

### Specification(Lower pressure type)

Type [Note1]	Tubing OD (mm)	Tubing ID (mm)	Wall Thickness (mm)	Package Length(m)	Working Pressure at 23°C(MPa)[Note2]	Burst pressure at 23°C(MPa)	Bend radius (mm)	Weight per 100M(kg)	Temperature (°C)
US98A080055□□	8.0	5.5	1.25	100	0.8	2.0	20	3.25	-20~70
US98A080060□□	8.0	6.0	1.00	100	0.4	1.5	25	2.70	
US98A100080□□	10.0	8.0	1.00	100	0.4	1.5	40	3.47	
US98A120100□□	12.0	10.0	1.00	100	0.4	1.5	60	4.24	
US98A160120□□	16.0	12.0	2.00	100	0.4	2.0	80	8.32	
UE95A080055□□	8.0	5.5	1.25	20/100	0.8	1.5	17	3.18	-40~70

[Note1] The first square of "□□" in the type column is for ordering code "unit" and the second is for "color".

[Note2] Working pressure:3 to 1 safety factor.

### Ordering code

#### US98A 060 040 100M BU



① Model	② Tubing OD	③ Tubing ID	④ Material length	⑤ Standard color [Note1]	
US98A: Ester Base, Shore A98±2	032: Φ3.2mm 040: Φ4.0mm 060: Φ6.0mm	020: Φ2.0mm 025: Φ2.5mm 040: Φ4.0mm 050: Φ5.0mm 055: Φ5.5mm 060: Φ6.0mm	065: Φ6.5mm 080: Φ8.0mm 0100: Φ10.0mm 0110: Φ11.0mm 0120: Φ12.0mm	100M: 100 m/coil 200M: 200 m/coil  100M: 100 m/coil	BU: Blue BK: Black C: Clear GE: Orange WH: White CB: Clear Blue R: Red Y: Yellow GA: Gray  GN: Green BR: Brown CR: Clear Red CG: Clear Green CY: Clear Yellow CE: Clear Orange
	UE95A: Ether Base, Shore A95±2	032: Φ3.2mm 040: Φ4.0mm 060: Φ6.0mm	020: Φ2.0mm 025: Φ2.5mm 040: Φ4.0mm 050: Φ5.0mm		

[Note1] Φ8xΦ6, Φ10xΦ8, Φ12xΦ10 type have nine standard colors: Blue\ Black\ Orange\ Clear\ White\ Clear Blue\ Red\ Yellow\ Gray.


## UCS Series



### Product feature

1. Plastic polyurethane material conforms to the ROHS environment protection requirement.
2. High elasticity: small bend radius enables PU tubing to pass through the tight space.
3. Anti-knot: better anti-knot effect than other plastic tubing.
4. Excellent flexibility: it can bear repeated expansion.
5. Anti-abrasion: long working life and suitable for the environment in which it is easy to be worn.
6. Low permeability of gas: relieve the problems of leakage and pollution.
7. Good anti-solubility: no solvent leaks, therefore it will not pollute the environment.
8. Low compression: maintain excellent physical character.
9. Wide resistance: it has certain resistance to chemicals, water, fuel, oil and bacterium.

### Technical chart



### Specification (Standard pressure type)

Type [Note1]	Tubing OD(mm)	Tubing ID(mm)	Working Pressure at 23°C(MPa) [Note2]	Burst pressure at 23°C(MPa)	Bend radius(mm)	Length(m) [Note3]	Temp. (°C)
UCS060040□030□□	6.0	4.0	1.0	3.0	38	3	-20~70
UCS060040□060□□	6.0	4.0	1.0	3.0	38	6	
UCS060040□090□□	6.0	4.0	1.0	3.0	38	9	
UCS060040□120□□	6.0	4.0	1.0	3.0	38	12	
UCS060040□150□□	6.0	4.0	1.0	3.0	38	15	
UCS080050□060□□	8.0	5.0	1.0	3.0	38	6	
UCS080050□090□□	8.0	5.0	1.0	3.0	38	9	
UCS080050□120□□	8.0	5.0	1.0	3.0	38	12	
UCS080050□150□□	8.0	5.0	1.0	3.0	38	15	
UCS100065□060□□	10.0	6.5	1.0	3.0	50	6	
UCS100065□090□□	10.0	6.5	1.0	3.0	50	9	
UCS100065□120□□	10.0	6.5	1.0	3.0	50	12	
UCS100065□150□□	10.0	6.5	1.0	3.0	50	15	
UCS120080□060□□	12.0	8.0	1.0	3.0	60	6	
UCS120080□090□□	12.0	8.0	1.0	3.0	60	9	
UCS120080□120□□	12.0	8.0	1.0	3.0	60	12	
UCS120080□150□□	12.0	8.0	1.0	3.0	60	15	

### Specification (Lower pressure type)

Type [Note1]	Tubing OD(mm)	Tubing ID(mm)	Working Pressure at 23°C(MPa) [Note2]	Burst pressure at 23°C(MPa)	Bend radius(mm)	Length(m) [Note3]	Temp. (°C)
UCS080055□060□□	8.0	5.5	0.8	2.0	38	6	-20~70
UCS080055□090□□	8.0	5.5	0.8	2.0	38	9	
UCS080055□120□□	8.0	5.5	0.8	2.0	38	12	
UCS080055□150□□	8.0	5.5	0.8	2.0	38	15	

[Note1] "□" in the type column is for "color", and "□□" is for "coupling type" and "coupling mode".

[Note2] Working pressure: 3 to 1 safety factor.

[Note3] Material length: length of operating status=(0.8~0.9)xMaterial length.

### Ordering code

UCS 080 050 BU 090M A 1						
① Model	② Tubing OD	③ Tubing ID	④ Standard color [Note1]	⑤ Material length	⑥ Coupling type	⑦ Coupling form
UCS: Ester Base	060: Φ6.0mm 080: Φ8.0mm 100: Φ10.0mm 120: Φ12.0mm	040: Φ4.0mm 050: Φ5.0mm 055: Φ5.5mm 065: Φ6.5mm 080: Φ8.0mm	BU: Blue BK: Black GE: Orange C: Clear WH: White CB: Clear Blue R: Red Y: Yellow GN: Green BR: Brown CR: Clear Red CG: Clear Green CY: Clear Yellow CE: Clear Orange	030M: 3m 060M: 6m 090M: 9m 120M: 12m 150M: 15m	A: one end is 30cm and the other end is 10cm B: Both of the tubings of the couplings are 10cm C: Both of the tubings of the couplings are 0cm	1: Without coupling 2: With female-male coupling 3: With male-male coupling

[Note1] Lower pressure type has nine standard colors: Blue\ Black\ Orange\ Clear\ White\ Clear Blue\ Red\ Yellow\ Gray.

### Pipe end coupling

Male quick coupling	Female quick coupling	Male quick coupling	Female quick coupling	Male quick coupling	Female quick coupling	Male quick coupling	Female quick coupling
PP40 Φ12 × Φ8	SP40 Φ12 × Φ8	PP30 Φ10 × Φ6.5	SP30 Φ10 × Φ6.5	PP20 Φ8 × Φ5	SP20 Φ8 × Φ5	PP10 Φ6 × Φ4	SP10 Φ6 × Φ4
PP40/SP40-PU tubing (12 × 8) quick coupling use		PP30/SP30-PU tubing (10 × 6.5) quick coupling use		PP20/SP20-PU tubing (8 × 5) quick coupling use		PP10/SP10-PU tubing (6 × 4) quick coupling use	